AcuKey - TouchPad

Non-Incendive Peripheral

ACCESSORIES









THE KB02-24-C1D2 IS NON INCENDIVE AND FEATURES AN INTEGRATED FORCE SENSING RESISTOR (FSR) POINTING DEVICE. IS ENCLOSED IN A STAINLESS STEEL CASE AND CARRIES A FACTORY MUTUAL APPROVAL OF CLASS I, DIVISION II. THESE UNITS ARE IDEAL FOR HARSH WORKING CON-DITIONS. ALL UNITS COME WITH ISOLATION BARRIER.















AcuKey - TouchPad

Non-Incendive Peripheral

ACCESSORIES



C1D2 PRE-CERTIFIED | WITH ISOLATION BARRIER

ENVIRONMENTAL

TEMP RANGE -20°C TO 60°C (-4°F TO 140°F)

STORAGE TEMP -40°C TO 85°C (-40°F TO 185°F)

RELATIVE HUMIDITY 100% (WHEN PROPERLY INSTALLED)

CERTIFICATIONS NEMA 4X UL60950, FCC PART 15 CLASS B, FACTORY MUTUAL: CLASS I DIV 2

GROUPS A, B, C, D CLASS II DIV 2 GROUPS F & G CLASS III DIV 2

MECHANICAL

COMPATABILITY USB KEYBOARD/FSR: ALL WINDOWS OPERATING SYSTEMS USB KEYBOARD/FSR:

ALL WINDOWS AND MACINTOSH OPERATING SYSTEMS

WEIGHT 6.15 LBS +/- 0.10 LBS (2.78 KG +/- 0.05 KG)

DIMENSIONS 14.2" x 5.70" x 1.24" (w-h-d) 361 MM X 145 MM X 31.5 MM

CONSTRUCTION STAINLESS STEEL, INDUSTRIAL SILICONE RUBBER

ELECTRICAL

POWER KEYBOARD: 5V@10MA (FROM CPU PORT) MOUSE: 5V@20MA

(FROM CPU PORT)

MODEL NUMBERS

CLASS I DIV 2 MDL # KB02-24-C1D2

ACURA EMBEDDED SYSTEMS INC.

#101 - 17825 64 AVE, SURREY BC

V3S 1Z3 CANADA

PHONE NUMBER: +1 (604) 502-9666 TOLL-FREE: 1-866-502-9666

WWW.ACURAEMBEDDED.COM EMAIL: CONTACT@ACURAEMBEDDED.COM